# The Equivalence of Semidefinite Relaxation MIMO Detectors for Higher-Order QAM

Wing-Kin Ma, Chao-Cheng Su, Joakim Jaldén, Tsung-Hui Chang, and Chong-Yung Chi

Abstract-In multi-input multi-output (MIMO) detection, semidefinite relaxation (SDR) has been shown to be an efficient high-performance approach. For BPSK and QPSK, it has been found that SDR can provide near-optimal bit error probability performance. This has stimulated a number of recent research endeavors that aim to apply SDR to the high-order QAM cases. These independently developed SDRs are different in concept, structure and complexity, and presently no serious analysis has been given to compare these methods. This paper analyzes the relationship of three such SDR methods, namely the polynomial-inspired SDR (PI-SDR) by Wiesel et al., the bound-constrained SDR (BC-SDR) by Sidiropoulos and Luo, and the virtually-antipodal SDR (VA-SDR) by Mao et al. Rather unexpectedly, we prove that the three SDRs are equivalent in the following sense: The three SDRs yield the same optimal objective values, and their optimal solutions have strong correspondences. Specifically, we establish this solution equivalence between BC-SDR and VA-SDR for any 4<sup>q</sup>-QAM constellations, and that between BC-SDR and PI-SDR for 16-QAM and 64-QAM. Moreover, the equivalence result holds for any channel, problem size, and signal-to-noise ratio. Our theoretical findings are confirmed by simulations, where the three SDRs offer identical symbol error probabilities. Additional simulation results are also provided to demonstrate the effectiveness of SDR compared to some other MIMO detectors, in terms of complexity and symbol error performance.

*Index Terms*—Convex optimization, multi-input multi-output (MIMO) detection, semidefinite programming (SDP), semidefinite relaxation (SDR).

## I. INTRODUCTION

ULTIPLE-INPUT multiple-output (MIMO) detection using semidefinite relaxation (SDR) [1]–[14] has recently received increasing attention. Being a symbol-constellation dependent technique, SDR has been shown to provide

Manuscript received September 01, 2008; revised July 24, 2009. Current version published January 13, 2010. This work was supported in part by a General Research Fund awarded by Research Grant Council, Hong Kong (Project No. CUHK 415908) and in part by the National Science Council, R.O.C., under Grants 96-2628-E-007-002-MY2 and NSC 96-2219-E-007-001. The work of J. Jaldén was supported by the STREP under Project IST-026905 (MASCOT) within the Sixth Framework Program of the European Commission. Part of this work was presented in ICASSP2008. The associate editor coordinating the review of this manuscript and approving it for publication was Dr. Gerald Matz.

W.-K. Ma is with the Department of Electronic Engineering, The Chinese University of Hong Kong, Shatin, N.T., Hong Kong (e-mail: wkma@ieee.org).

C.-C. Su is with the Sunplus, Inc., Hsinchu 30078, Taiwan (e-mail: g9564512@oz.nthu.edu.tw).

J. Jaldén is with the School of Electrical Engineering, Signal Processing, The Royal Institute of Technology (KTH), SE-100 44 Stockholm, Sweden (e-mail: joakim.jalden@ee.kth.se).

T.-H. Chang and C.-Y. Chi are with the Institute of Communications Engineering and Department of Electrical Engineering, National Tsing Hua University, Hsinchu 30013, Taiwan (e-mail: changth@mx.nthu.edu.tw; cychi@ee. nthu.edu.tw).

Color versions of one or more of the figures in this paper are available online at http://ieeexplore.ieee.org.

Digital Object Identifier 10.1109/JSTSP.2009.2035798

considerably better symbol error performance than some suboptimal MIMO detectors such as the linear and decision-feedback receivers. SDR is not an optimal approach from a maximum-likelihood (ML) perspective, but it guarantees a polynomial-time complexity in the problem dimension. In comparison, the currently best known methods for optimal ML MIMO detection, namely sphere decoding [15], [16], do not have such a guarantee [17].<sup>1</sup>

SDR was first proposed for the BPSK constellation [1], [2], and the same idea can easily be carried forward to the QPSK constellation (or 4-QAM) [6], [7]. For BPSK and QPSK, simulation results have indicated that SDR can provide near-optimal bit error performance. This intriguing finding has stimulated a number of works. Theoretically, it is shown recently [13] that SDR can achieve the full receive diversity in the BPSK case. An equally interesting but totally different analysis is given in [14], where the SDR approximation gap is examined using random matrix theory. Apart from theoretical analysis, there has been interest in various aspects such as fast implementations [19], [20] and soft-in-soft-out MIMO detection [7], [21].

However, what attracts more attention in SDR is possibly its extension to more general symbol constellations, especially the higher order QAM. SDR for higher order PSK has been considered in [3]. For higher order QAM which is the focus of this paper, the first endeavor is by Wiesel et al. [9], who proposed a polynomial-inspired SDR (PI-SDR) method for 16-QAM. In that work, the authors also showed that PI-SDR is a bidual of the optimal ML MIMO detector (or achieves an optimal Lagrangian dual lower bound of the ML metric). The drawback of PI-SDR is that its extension to larger QAM sizes would be increasingly complex to handle. Later, Sidiropoulos and Luo proposed a bound-constrained SDR (BC-SDR) method [9] for any QAM constellation. BC-SDR aims at simplicity and appears to be less sophisticated than PI-SDR. For instance, the BC-SDR problem structure is virtually the same for any QAM size. The simple, special structures of BC-SDR make fast implementations [22] particularly favorable. More recently, Mao et al. [10] developed a virtually-antipodal SDR (VA-SDR) method for any  $4^q$ -QAM (where  $q \ge 1$ ). As its name implies, VA-SDR has a strong connection to the SDR used in BPSK/QPSK. VA-SDR is structurally less complex than PI-SDR, but involves more optimization variables than BC-SDR.

It is worthwhile to mention two more recent developments. Mobasher *et al.* formulated a class of SDR problems that is applicable to any kind of symbol constellations [12]. As a price

<sup>1</sup>As a short aside, the complexity limitation of optimal sphere decoding has recently motivated interest in some suboptimal but reduced-complexity variants; e.g., the Fano decoder [16] and the fixed-complexity sphere decoder [18].

for their generality, Mobasher's formulations are considerably more complex than the other SDRs. This translates into a higher computational requirement. Yang *et al.* [11] proposed a tightened version of BC-SDR for the 16-QAM case. Interestingly, they showed that their tightened BC-SDR can provide a better approximation than the 16-QAM PI-SDR.

While a number of SDR methods have been proposed for higher order QAM, their comparisons have not been seriously considered at present. This paper focuses on analyzing the relationship of the PI-SDR, BC-SDR, and VA-SDR methods. We obtain a result that is intuitively not so obvious: *PI-SDR*, *BC-SDR*, and VA-SDR are actually equivalent, despite the fact that they exhibit rather different structures and complexities. Specifically, our analysis reveals the following:

- 1) for 16-QAM and 64-QAM, there exists an equivalence between the feasible sets of PI-SDR and BC-SDR;
- 2) for any 4<sup>*q*</sup>-QAM, there exists an equivalence between the feasible sets of VA-SDR and BC-SDR.

This feasible set equivalence directly translates into equivalence of the solution sets of the three SDRs. Hence, the three SDRs are expected to provide the same symbol error probability. This is further illustrated by simulations. Moreover, the equivalence result is quite general in the sense that it holds for any channel, problem size, and signal-to-noise ratio (SNR).

This paper is organized as follows. In order to give insights into the three SDRs, we use the relatively simple case of 16-QAM to provide the problem statement in Section II, and to review the three SDR methods in Section III. This is followed by Section IV, where we provide numerical comparisons of the three SDRs. In particular, the complexity and performance of the three SDRs will be shown and compared. Then, in Section V we prove the 16-QAM SDR equivalence, with an emphasis on illustrating the main ideas (which would be difficult to see for the more complex cases of larger QAM sizes). As a step further, Section VI proves the SDR equivalence for larger QAM sizes. Some simulation results are provided in Section VII for demonstrating the SDR performance.

#### **II. PROBLEM STATEMENT**

The MIMO detection problem may be most easily described by considering the standard scenario of spatial multiplexing (or V-BLAST) over a frequency-flat channel [23], [24]. In that scenario, we have the transmitter and receiver equipped with  $\tilde{N}$  and  $\tilde{M}$  antennas, respectively, and each transmitter antenna sends an independent data symbol at each symbol interval. The received spatial signal can be modeled by the following formula:

$$\tilde{\mathbf{y}} = \tilde{\mathbf{H}}\tilde{\mathbf{s}} + \tilde{\boldsymbol{\nu}}.$$
 (1)

Here,  $\tilde{\mathbf{H}} \in \mathbb{C}^{\tilde{M} \times \tilde{N}}$  is the MIMO channel,  $\tilde{\mathbf{y}} \in \mathbb{C}^{\tilde{M}}$  is the received signal vector,  $\tilde{\boldsymbol{\nu}}$  is a noise vector assumed to be zero-mean circular white Gaussian, and  $\tilde{\mathbf{s}} \in S^{\tilde{N}}$  is the transmitted symbol vector where  $S \subset \mathbb{C}$  denotes the symbol constellation set. For the 16-QAM constellation, S is given by

$$\mathcal{S} = \{s = s_R + js_I | s_R, s_I \in \{\pm 1, \pm 3\}\}.$$

It should be emphasized that detection techniques for (1), or simply MIMO detection, is a very meaningful topic with relevance not only to spatial multiplexing but also to many other scenarios. In CDMA multiuser detection [25], for instance, the respective detection problem can be formulated in the same form as (1) (with  $\tilde{N}$  becoming the number of users). Likewise, in the decoding of some space–time block codes [26] and space–frequency block codes [27], we are confronted with a detection problem in which the model can eventually be formulated as (1). For a detailed description of these, we refer the reader to [15], [16] which provide an excellent coverage of how the simple model in (1) can be relevant to many different detection problems in communications.

It is convenient to reformulate the complex-valued model in (1) to a real-valued one. Let

$$\mathbf{y} = \begin{bmatrix} \Re\{\tilde{\mathbf{y}}\}\\\Im\{\tilde{\mathbf{y}}\}\end{bmatrix}, \quad \mathbf{s} = \begin{bmatrix} \Re\{\tilde{\mathbf{s}}\}\\\Im\{\tilde{\mathbf{s}}\}\end{bmatrix}$$
$$\mathbf{H} = \begin{bmatrix} \Re\{\tilde{\mathbf{H}}\} & -\Im\{\tilde{\mathbf{H}}\}\\\Im\{\tilde{\mathbf{H}}\} & \Re\{\tilde{\mathbf{H}}\}\end{bmatrix}$$

 $M = 2\tilde{M}$ , and  $N = 2\tilde{N}$ . Equation (1) is equivalent to

$$\mathbf{y} = \mathbf{H}\mathbf{s} + \boldsymbol{\nu} \tag{2}$$

where  $\mathbf{s} \in \{\pm 1, \pm 3\}^N$  and  $\boldsymbol{\nu}$  is defined in the same way as  $\mathbf{y}$ . The ML detection problem for the MIMO model in (2) is shown to be an optimization problem

$$\min_{\mathbf{s} \in \{\pm 1, \pm 3\}^N} \|\mathbf{y} - \mathbf{Hs}\|^2 \tag{3}$$

in which the globally optimal solution serves as the ML decision. Note that  $|| \cdot ||$  in (3) stands for the vector 2-norm. ML detection is known to provide superior detection performance, but the major challenge lies in solving (3) which is a computationally hard problem. Presently, the best known optimal solver for (3) is sphere decoding [15], [16]. While sphere decoding has been empirically found to be computationally very fast for small to moderate problem sizes (say, for  $N \leq 20$  for 16-QAM), it has been revealed [17] that the sphere decoding complexity would be prohibitive for large N and/or low SNRs.

## III. REVIEW OF THREE 16-QAM SDR DETECTORS

SDR is a suboptimal approach to ML, using a class of polynomial-time solvable convex optimization problems known as semidefinite programs. In this section, we review three SDR methods for the 16-QAM constellation, namely PI-SDR [8], BC-SDR [9], and VA-SDR [10]. (Their extensions beyond 16-QAM will be considered later in the paper.)

# A. Polynomial Inspired SDR

PI-SDR was the first application of the SDR principle [28] to 16-QAM ML detection, to the best of our knowledge. To present its idea, consider a reformulation of the ML problem in (3)

$$\min_{\mathbf{S}\in\mathbb{S}^{N},\mathbf{s}\in\mathbb{R}^{N}} \quad \operatorname{tr}(\mathbf{H}^{T}\mathbf{H}\mathbf{S}) - 2\mathbf{s}^{T}\mathbf{H}^{T}\mathbf{y} + \|\mathbf{y}\|^{2}$$
  
s.t.  $\mathbf{S} = \mathbf{s}\mathbf{s}^{T}, \quad S_{ii} \in \{1,9\}, \ i = 1, \dots, N$  (4)

where **S** is a slack variable,  $\mathbb{S}^N$  is the set of  $N \times N$  real symmetric matrices,  $S_{ij}$  denotes the (i, j)th element of **S**, and tr( $\cdot$ ) is the trace operator. PI-SDR was inspired by the fact that

$$u \in \{1,9\} \Longleftrightarrow (u-1)(u-9) = 0 \Longleftrightarrow u^2 - 10u + 9 = 0.$$

By turning the constraints  $S_{ii} \in \{1, 9\}$  to a polynomial form, Problem (4) is further reformulated as

$$\min_{\mathbf{S}, \mathbf{s}, \mathbf{U}, \mathbf{u}} \quad \operatorname{tr}(\mathbf{H}^T \mathbf{H} \mathbf{S}) - 2\mathbf{s}^T \mathbf{H}^T \mathbf{y} + \|\mathbf{y}\|^2$$
s.t.  $\mathbf{S} = \mathbf{s}\mathbf{s}^T, \quad \mathbf{U} = \mathbf{u}\mathbf{u}^T$ 
 $d(\mathbf{S}) = \mathbf{u}, \quad d(\mathbf{U}) - 10\mathbf{u} + 9\mathbf{1}_N = \mathbf{0}$  (5)

where  $d : \mathbb{R}^{N \times N} \to \mathbb{R}^N$  is the diagonal operator (i.e.,  $d(\mathbf{S}) = [S_{11}, \ldots, S_{NN}]^T$ ), and  $\mathbf{1}_N$  is the N-dimensional all-one vector. The reformulated ML problem in (5) is still hard, where the difficulty lies in the nonconvex constraints  $\mathbf{S} = \mathbf{ss}^T$  and  $\mathbf{U} = \mathbf{uu}^T$  which restrict  $\mathbf{S}$  and  $\mathbf{U}$  to be of rank 1. In PI-SDR, we relax the polynomial ML formulation in (5) to

min tr(
$$\mathbf{H}^{T}\mathbf{HS}$$
) - 2s<sup>T</sup> $\mathbf{H}^{T}\mathbf{y}$  +  $||\mathbf{y}||^{2}$   
s.t.  $\mathbf{S} \succeq \mathbf{ss}^{T}$ ,  $\mathbf{U} \succeq \mathbf{uu}^{T}$   
 $d(\mathbf{S}) = \mathbf{u}$ ,  $d(\mathbf{U}) - 10\mathbf{u} + 9\mathbf{1}_{N} = \mathbf{0}$  (6)

where  $\mathbf{A} \succeq \mathbf{B}$  means that  $\mathbf{A} - \mathbf{B}$  is positive semidefinite (PSD). The idea is to replace the hard constraint  $\mathbf{S} = \mathbf{ss}^T$  by a convex constraint  $\mathbf{S} \succeq \mathbf{ss}^T$ , and similarly to  $\mathbf{U} = \mathbf{uu}^T$ . There are two basic advantages with such a relaxation. First, Problem (6), or the PI-SDR problem is a semidefinite program (SDP) which is convex and does not suffer from local minima. Second, as an SDP the PI-SDR problem can be solved by available interiorpoint methods [29], [30] in a polynomial-time fashion.

Once we solve the PI-SDR problem in (6), we can make a symbol decision by simple rounding of the PI-SDR solution associated with s. A better alternative to this simple rounding is the Gaussian randomized rounding; see [2], [8], and [9] for the details.

#### B. Bound Constrained SDR

BC-SDR is possibly the simplest among the various 16-QAM SDR methods. It relaxes the ML problem in (4) to an SDP

min tr(
$$\mathbf{H}^T \mathbf{H} \mathbf{S}$$
) - 2s<sup>T</sup> $\mathbf{H}^T \mathbf{y} + ||\mathbf{y}||^2$   
s.t.  $\mathbf{S} \succeq \mathbf{ss}^T$ ,  $1 \le S_{ii} \le 9$ ,  $i = 1, \dots, N$  (7)

where the original constraint  $\mathbf{S} = \mathbf{s}\mathbf{s}^T$  is replaced by the PSD constraint  $\mathbf{S} \succeq \mathbf{s}\mathbf{s}^T$  (as in PI-SDR), and the discrete set  $\{1,9\}$  is relaxed to an interval [1,9].

The BC-SDR problem in (7) exhibits particularly simple SDP problem structure. This has enabled us to develop a specialized interior-point algorithm for (7) that runs many times faster than some general-purpose interior-point software [22]. The complexity of BC-SDR is shown to be  $O(N^{3.5})$  [22].

### C. Virtually Antipodal SDR

VA-SDR was proposed by Mao *et al.* [10].<sup>2</sup> The idea stems from the fact that

$$s \in \{\pm 1, \pm 3\} \iff s = b_1 + 2b_2, \quad b_1, b_2 \in \{\pm 1\}.$$

Hence, the 16-QAM ML problem can be re-expressed in a virtually antipodal form

$$\min_{\mathbf{b}_1, \mathbf{b}_2 \in \{\pm 1\}^N} \|\mathbf{y} - \mathbf{H}(\mathbf{b}_1 + 2\mathbf{b}_2)\|^2 = \min_{\mathbf{b} \in \{\pm 1\}^{2N}} \|\mathbf{y} - \mathbf{H}\mathbf{W}\mathbf{b}\|^2$$
(8)

where we denote

$$\mathbf{W} = [\mathbf{I} \quad 2\mathbf{I}], \quad \mathbf{b} = [\mathbf{b}_1^T \quad \mathbf{b}_2^T]^T$$

By applying the same SDR as in BPSK/QPSK constellations, VA-SDR is obtained

min tr(
$$\mathbf{W}^T \mathbf{H}^T \mathbf{H} \mathbf{W} \mathbf{B}$$
) - 2 $\mathbf{b}^T \mathbf{W}^T \mathbf{H}^T \mathbf{y} + ||\mathbf{y}||^2$   
s.t.  $\mathbf{B} \succeq \mathbf{b} \mathbf{b}^T$ ,  $B_{ii} = 1$ ,  $i = 1, \dots, 2N$ . (9)

In terms of problem structure, VA-SDR is exactly the same as the SDR for BPSK/QPSK. Hence, VA-SDR can be implemented by directly applying interior-point algorithms designed for BPSK/QPSK SDR [20], [29].

#### IV. NUMERICAL COMPARISONS OF THE THREE 16-QAM SDRS

In order to shed some light into the performance and complexity of the three 16-QAM SDR methods, let us use simulations to compare the three methods before proceeding to the theoretical analysis in the next section. The simulation setting follows that of a standard MIMO system, where the channel matrix  $\tilde{\mathbf{H}}$  is independent and identically distributed (i.i.d.) complex circular Gaussian distributed with zero mean and unit variance. The MIMO system size is  $(\tilde{M}, \tilde{N}) = (8, 8)$ . For PI-SDR and BC-SDR, we employ the *simple rounding* procedure; i.e., if s<sup>\*</sup> is the PI-SDR/BC-SDR solution associated with s, then

$$\hat{\mathbf{s}} = \operatorname{dec}(\mathbf{s}^{\star})$$

is the detected symbol vector where dec(·) is the elementwise decision function for the discrete set  $\{\pm 1, \pm 3\}$ . For VA-SDR, there are two possible ways of doing simple rounding. Let  $\mathbf{b}^* = [(\mathbf{b}_1^*)^T (\mathbf{b}_2^*)^T]^T$ ,  $\mathbf{b}_1^*$ ,  $\mathbf{b}_2^* \in \mathbb{R}^N$ , be the VA-SDR solution associated with **b**. We can detect **s** either by

$$\hat{\mathbf{s}} = \operatorname{sgn}(\mathbf{b}_1^{\star}) + 2\operatorname{sgn}(\mathbf{b}_2^{\star}) \tag{10}$$

where  $sgn(\cdot)$  denotes the elementwise sign function, or by

$$\hat{\mathbf{s}} = \operatorname{dec}(\mathbf{b}_1^{\star} + 2\mathbf{b}_2^{\star}) = \operatorname{dec}(\mathbf{W}\mathbf{b}^{\star}).$$
(11)

<sup>2</sup>In fact, an earlier work by Steingrimsson *et al.* [7] was close to finding VA-SDR. In that paper, a symbol is considered as a linear transformation of antipodal bits, which is exactly how VA-SDR works. But we should emphasize that it was Mao *et al.* [10] who first described the use of VA-SDR for higher order QAM and put the method to the test.

Authorized licensed use limited to: National Tsing Hua University. Downloaded on January 14, 2010 at 03:51 from IEEE Xplore. Restrictions apply



Fig. 1. Performance comparison of PI-SDR, BC-SDR, and VA-SDR in an  $8 \times 8$  16-QAM system. (a) Symbol error rates versus SNRs. (b) Optimal objective values versus SNRs. (c) Optimal objective values versus problem sizes.

We call (10) and (11) *simple rounding I* and *simple rounding II*, respectively.

The simulated symbol error performance of the three SDRs is given in Fig. 1(a). In the figure the SNR is defined as the received signal-to-noise ratio per QAM symbol; i.e.,  $E\{||\tilde{\mathbf{h}}_i\tilde{s}_i||^2\}/E\{||\tilde{\boldsymbol{\nu}}||^2\}$ . One can see that for VA-SDR, simple



Fig. 2. Comparison of complexities of PI-SDR, BC-SDR, and VA-SDR in a 16-QAM system.

rounding II gives better performance than simple rounding I, but, more importantly, the performance of PI-SDR, BC-SDR, and VA-SDR (with simple rounding II) is identical. To get further insights, we evaluated the respective optimal objective function values achieved by the three SDRs. The result, shown in Fig. 1(b) indicates that they all look identical. In Fig. 1(c) the optimal objective values of the three SDRs are plotted with respect to the problem size  $\tilde{N}$ , where the same phenomenon is seen. From these observation it is reasonable to suspect that there are strong connections between the three SDRs.

Now let us compare the complexities of the three SDRs. For fairness of comparison, the three SDRs were implemented by the same SDP solver, namely the general-purpose SDP software SeDuMi [30]. The complexities, in term of average running time, are plotted in Fig. 2. We can see that BC-SDR yields the lowest complexity, while VA-SDR and PI-SDR have similar computational times with PI-SDR being slightly more expensive. Thus, based on Figs. 1 and 2, we see that the application of BC-SDR in place of VA-SDR or PI-SDR leads to an order of magnitude reduction in computational time with no performance degradation.

## V. EQUIVALENCE OF THE THREE 16-QAM SDR DETECTORS

In this section, we prove the equivalence of PI-SDR, BC-SDR, and VA-SDR in the 16-QAM case. In the first subsection, the main result will be described. Then, the analysis leading to the equivalence result will be shown in detail in the second and third subsections.

#### A. Main Result and Implications

The three SDRs can be represented by a unified expression

$$\min_{(\mathbf{S},\mathbf{s})\in\mathcal{F}} \quad f(\mathbf{S},\mathbf{s}) \tag{12}$$

where

$$f(\mathbf{S}, \mathbf{s}) = \operatorname{tr}(\mathbf{H}^T \mathbf{H} \mathbf{S}) - 2\mathbf{s}^T \mathbf{H}^T \mathbf{y} + ||\mathbf{y}||^2$$

is the objective function, and  $\mathcal{F}$  is the feasible set, the definition of which depends on the SDR method employed. For BC-SDR, the feasible set is defined as

$$\mathcal{F}_{\mathsf{BC-SDR}} = \{ (\mathbf{S}, \mathbf{s}) | \mathbf{S} \succeq \mathbf{s} \mathbf{s}^T, \mathbf{1}_N \preceq d(\mathbf{S}) \preceq 9 \mathbf{1}_N \}.$$
(13)

(We adopt the standard notation that " $\preceq$ " and " $\succeq$ " mean elementwise inequalities, when applied on vectors). For PI-SDR, the feasible set is characterized as shown in (14) and (15) at the bottom of the page, and for VA-SDR

$$\mathcal{F}_{\mathsf{VA-SDR}} = \left\{ (\mathbf{S}, \mathbf{s}) = (\mathbf{W}\mathbf{B}\mathbf{W}^T, \mathbf{W}\mathbf{b}) | (\mathbf{B}, \mathbf{b}) \in \mathcal{B}_{\mathsf{VA-SDR}} \right\}$$
(16)

$$\mathcal{B}_{VA-SDR} = \{ (\mathbf{B}, \mathbf{b}) | \mathbf{B} \succeq \mathbf{b} \mathbf{b}^T, \ d(\mathbf{B}) = \mathbf{1}_{2N} \}.$$
(17)

Essentially, the equivalence of the three SDRs lies in the feasible set:

Theorem 1: The feasible sets of the three 16-QAM SDRs are identical; that is

$$\mathcal{F}_{PI-SDR} = \mathcal{F}_{BC-SDR} = \mathcal{F}_{VA-SDR}$$
.

The proof will be described in the next two subsections. From Theorem 1 we make the following important conclusion.

Corollary 1: For 16-QAM MIMO detection, the relaxation problems of PI-SDR, BC-SDR, and VA-SDR [given in (6), (7), and (9), respectively] are equivalent. In particular:

- if (Û, ũ, Ŝ, ŝ) is an optimal solution of PI-SDR, then (Ŝ, ŝ) is an optimal solution of BC-SDR;
- 2) if (B, b) is an optimal solution of VA-SDR, then (WBW<sup>T</sup>, Wb) is an optimal solution of BC-SDR;
- if (S<sup>\*</sup>, s<sup>\*</sup>) is an optimal solution of BC-SDR, then there exists (U<sup>\*</sup>, u<sup>\*</sup>) such that (U<sup>\*</sup>, u<sup>\*</sup>, S<sup>\*</sup>, s<sup>\*</sup>) is an optimal solution of PI-SDR;
- 4) if (S<sup>\*</sup>, s<sup>\*</sup>) is an optimal solution of BC-SDR, then there exists (B<sup>\*</sup>, b<sup>\*</sup>) such that (WB<sup>\*</sup>W<sup>T</sup>, Wb<sup>\*</sup>) = (S<sup>\*</sup>, s<sup>\*</sup>) and (B<sup>\*</sup>, b<sup>\*</sup>) is an optimal solution of VA-SDR.

Some further discussions are as follows.

- From Corollary 1 we see that an optimal BC-SDR solution can be directly obtained from an optimal PI-SDR or VA-SDR solution. In fact, our proof also reveals that an optimal PI-SDR or VA-SDR solution can also be constructed from an optimal BC-SDR solution in a direct, closed-form manner. For the construction details readers are referred to the proof in the following subsections.
- 2) The three SDRs can be proven to be equivalent for larger QAM sizes. For the equivalence of VA-SDR and BC-SDR, the proof can be generalized using a similar principle, but, for the equivalence of PI-SDR and BC-SDR, the proof is

much harder and tedious even for 64-QAM. This will be elaborated upon in the next section.

The proof of Theorem 1 consists of two parts: proving that  $\mathcal{F}_{BC-SDR} = \mathcal{F}_{PI-SDR}$ , and  $\mathcal{F}_{BC-SDR} = \mathcal{F}_{VA-SDR}$ .

B. First Part of the Proof of Theorem 1:  $\mathcal{F}_{BC-SDR} = \mathcal{F}_{PI-SDR}$ 

We first show that if  $(\mathbf{U}, \mathbf{u}, \mathbf{S}, \mathbf{s}) \in \mathcal{W}_{\mathsf{PI-SDR}}$ , then  $(\mathbf{S}, \mathbf{s})$ is feasible to  $\mathcal{F}_{\mathsf{BC-SDR}}$ . Given  $(\mathbf{U}, \mathbf{u}, \mathbf{S}, \mathbf{s}) \in \mathcal{W}_{\mathsf{PI-SDR}}$ , the PI-SDR feasibility condition  $\mathbf{U} \succeq \mathbf{u}\mathbf{u}^T$  implies that  $U_{ii} \ge u_i^2$ for all  $i = 1, \ldots, N$ . Hence,

$$0 = U_{ii} - 10u_i + 9 \ge u_i^2 - 10u_i + 9$$
  
=  $(u_i - 1)(u_i - 9)$ 

for all *i*. The inequality above is the same as  $(S_{ii}-1)(S_{ii}-9) \le 0$ , or  $1 \le S_{ii} \le 9$ . This shows that  $(\mathbf{S}, \mathbf{s}) \in \mathcal{F}_{\mathsf{BC-SDR}}$ .

Next, we show that for any  $(\mathbf{S}, \mathbf{s}) \in \mathcal{F}_{\mathsf{BC-SDR}}$ , we can explicitly construct a  $(\mathbf{U}, \mathbf{u})$  such that  $(\mathbf{U}, \mathbf{u}, \mathbf{S}, \mathbf{s}) \in \mathcal{W}_{\mathsf{PI-SDR}}$ . Consider the following construction from  $(\mathbf{S}, \mathbf{s}) \in \mathcal{F}_{\mathsf{BC-SDR}}$ :

$$\mathbf{u} = d(\mathbf{S})$$
$$\mathbf{U} = \mathbf{u}\mathbf{u}^T + D(\mathbf{w})$$
(18)

where  $D: \mathbb{R}^N \to \mathbb{R}^{N \times N}$  is the operator that outputs a diagonal matrix with its main diagonals being the input, and **w** is given by

$$w_i = -(S_{ii} - 1)(S_{ii} - 9) = -(u_i - 1)(u_i - 9)$$
(19)

for i = 1, ..., N. Since  $1 \le S_{ii} \le 9$ , we have  $w_i \ge 0$ . It follows that  $\mathbf{U} - \mathbf{u}\mathbf{u}^T = D(\mathbf{w}) \succeq \mathbf{0}$ . Moreover, from (18)–(19), one can see that

$$U_{ii} - 10u_i + 9 = w_i + u_i^2 - 10u_i + 9 = 0$$

for all *i*. This proves that  $(\mathbf{U}, \mathbf{u}, \mathbf{S}, \mathbf{s})$  is feasible to  $\mathcal{W}_{\mathsf{PI}-\mathsf{SDR}}$ .

The proof above indicates that whenever a point is feasible to  $\mathcal{F}_{PI-SDR}$  it is also feasible to  $\mathcal{F}_{BC-SDR}$ , and vice versa. We therefore conclude that  $\mathcal{F}_{BC-SDR} = \mathcal{F}_{PI-SDR}$ .

# C. Second Part of the Proof of Theorem 1: $\mathcal{F}_{VA-SDR} = \mathcal{F}_{BC-SDR}$

Let  $\mathbf{X} \in \mathbb{S}^{N+1}$  and  $\mathbf{Y} \in \mathbb{S}^{2N+1}$  be two PSD matrices taking the form

$$\mathbf{X} = \begin{bmatrix} \mathbf{S} & \mathbf{s} \\ \mathbf{s}^T & 1 \end{bmatrix} \succeq \mathbf{0}, \quad \mathbf{Y} = \begin{bmatrix} \mathbf{B} & \mathbf{b} \\ \mathbf{b}^T & 1 \end{bmatrix} \succeq \mathbf{0}$$

where  $(\mathbf{S}, \mathbf{s}) \in \mathbb{S}^N \times \mathbb{R}^N$ ,  $(\mathbf{B}, \mathbf{b}) \in \mathbb{S}^{2N} \times \mathbb{R}^{2N}$ . By Schur complement, the two matrices satisfy  $\mathbf{S} \succeq \mathbf{ss}^T$  and  $\mathbf{B} \succeq \mathbf{bb}^T$ .

$$\mathcal{F}_{\mathsf{PI-SDR}} = \{ (\mathbf{S}, \mathbf{s}) \mid (\mathbf{U}, \mathbf{u}, \mathbf{S}, \mathbf{s}) \in \mathcal{W}_{\mathsf{PI-SDR}} \}$$
(14)

$$\mathcal{W}_{\mathsf{PI-SDR}} = \left\{ (\mathbf{U}, \mathbf{u}, \mathbf{S}, \mathbf{s}) | \mathbf{U} \succeq \mathbf{u} \mathbf{u}^T, \ \mathbf{S} \succeq \mathbf{s} \mathbf{s}^T, \ d(\mathbf{S}) = \mathbf{u}, \ d(\mathbf{U}) - 10\mathbf{u} + 9\mathbf{1}_N = \mathbf{0} \right\}$$
(15)

We assume  $(S, s) = (WBW^T, Wb)$ , and this condition can be expressed in a matrix form

$$\mathbf{X} = \mathbf{T}^T \mathbf{Y} \mathbf{T} \tag{20}$$

where

$$\mathbf{T} = \begin{bmatrix} \mathbf{W}^T & \mathbf{0} \\ \mathbf{0} & 1 \end{bmatrix}.$$
 (21)

Since  $Y \succeq 0$ , Y can always be represented in a square-root factorization form

$$\mathbf{Y} = \mathbf{R}^T \mathbf{R}$$

for some square root factor  $\mathbf{R} = [\mathbf{r}_1, \dots, \mathbf{r}_{2N+1}] \in \mathbb{R}^{(2N+1)\times(2N+1)}$ , with  $||\mathbf{r}_{2N+1}|| = 1$  (owing to  $||\mathbf{r}_i||^2 = Y_{ii}$ and  $Y_{2N+1,2N+1} = 1$ ). Similarly, **X** can be characterized as

$$\mathbf{X} = \mathbf{Z}^T \mathbf{Z}$$

for some square root factor  $\mathbf{Z} = [\mathbf{z}_1, \dots, \mathbf{z}_{N+1}] \in \mathbb{R}^{(2N+1)\times(N+1)}, \|\mathbf{z}_{N+1}\| = 1$ . We see that (20) holds if

$$\mathbf{Z} = \mathbf{RT}.$$
 (22)

Let us partition

$$\mathbf{R} = \begin{bmatrix} \mathbf{U} & \mathbf{V} & \mathbf{r}_{2N+1} \end{bmatrix}$$
(23)

where  $\mathbf{U}, \mathbf{V} \in \mathbb{R}^{(2N+1) \times N}$ . Substituting (22) into (21), we see that  $\mathbf{Z} = [\mathbf{U} + 2\mathbf{V} | \mathbf{r}_{2N+1} ]$ , or equivalently

$$\mathbf{z}_i = \mathbf{u}_i + 2\mathbf{v}_i \qquad i = 1, \dots, N$$
$$\mathbf{z}_{N+1} = \mathbf{r}_{2N+1} \tag{24}$$

where  $\mathbf{u}_i$  is the *i*th column of  $\mathbf{U}$ , and  $\mathbf{v}_i$  is defined in a similar way.

Now, suppose  $(\mathbf{B}, \mathbf{b}) \in \mathcal{B}_{VA-SDR}$ . Since  $d_i(\mathbf{B}) = 1$  for all i(where  $d_i(\cdot)$  means that  $d_i(\mathbf{A}) = A_{ii}$ ), we have  $||\mathbf{u}_i|| = Y_{ii} = d_i(\mathbf{B}) = 1$  and  $||\mathbf{v}_i|| = Y_{i+N,i+N} = d_{i+N}(\mathbf{B}) = 1$  for  $i = 1, \ldots, N$ . With (23)–(24) satisfied, it holds true that

$$||\mathbf{z}_i|| \le ||\mathbf{u}_i|| + 2||\mathbf{v}_i|| = 3$$
  
 $||\mathbf{z}_i|| \ge 2||\mathbf{v}_i|| - ||\mathbf{u}_i|| = 1$ 

for i = 1, ..., N. This translates into an **S** that satisfies  $d_i(\mathbf{S}) = X_{ii} = ||\mathbf{z}_i||^2 \in [1, 9]$ , and this further implies that  $(\mathbf{S}, \mathbf{s}) \in \mathcal{F}_{BC-SDR}$ . On the other hand, suppose  $(\mathbf{S}, \mathbf{s}) \in \mathcal{F}_{BC-SDR}$ . There is no problem for (24) to be satisfied, and we find  $(\mathbf{u}_i, \mathbf{v}_i)$  satisfying (23) by resorting to the following lemma:

Lemma 1: Let  $\mathbf{z} \in \mathbb{R}^n$ ,  $n \geq 2$  be a given vector satisfying

$$\beta - \alpha \le \|\mathbf{z}\| \le \beta + \alpha$$

for some  $\alpha, \beta > 0$ . Then there exist two unit 2-norm vectors **u** and **v** such that

$$\mathbf{z} = \alpha \mathbf{u} + \beta \mathbf{v}.$$

The proof of Lemma 1 is given in Appendix A. Essentially, the proof shows how to construct  $(\mathbf{u}, \mathbf{v})$  from  $\mathbf{z}$  in a closed-form

manner. Applying Lemma 1 to (23) (with  $\alpha = 1$  and  $\beta = 2$ ), for each *i* we obtain  $(\mathbf{u}_i, \mathbf{v}_i)$  that satisfies (23) for any  $||\mathbf{z}_i|| \in [1,3]$ (or  $d_i(\mathbf{S}) \in [1,9]$ ) and then achieves  $||\mathbf{u}_i|| = ||\mathbf{v}_i|| = 1$  at the same time. This means that the resultant  $\mathbf{R}$  [cf., (22)] has unit 2-norm columns, and as a consequence  $d_i(\mathbf{B}) = Y_{ii} = ||\mathbf{z}_i||^2 =$ 1. Hence, we have  $(\mathbf{B}, \mathbf{b}) \in \mathcal{B}_{VA-SDR}$ .

We have shown by construction that  $\mathcal{F}_{VA-SDR} = \mathcal{F}_{BC-SDR}$ .

### VI. GENERALIZATIONS TO LARGER QAM SIZES

Now our attention turns to more challenging cases of larger QAM sizes. In what follows, we will prove that 1) for any  $4^{q}$ -QAM (where  $q \ge 1$ ), VA-SDR is equivalent to BC-SDR; and that 2) for the 64-QAM, PI-SDR is equivalent to BC-SDR. Details regarding 1) and 2) will be described in the first and second subsections, respectively. Numerical results for verifying the equivalence will then be provided in the third subsection.

## A. Equivalence of VA-SDR and BC-SDR for $4^{q}$ -QAM

For  $4^{q}$ -QAM, the ML problem to be addressed is

min 
$$\|\mathbf{y} - \mathbf{Hs}\|^2$$
  
s.t.  $s_i \in \{\pm 1, \pm 3, \pm 5, \dots, \pm (2^q - 1)\}, \quad i = 1, \dots, N.$ 

Its virtually antipodal formulation takes the form

$$\min_{\mathbf{b} \in \{\pm 1\}^{qN}} ||\mathbf{y} - \mathbf{HWb}||^2$$

where

$$\mathbf{W} = \begin{bmatrix} \mathbf{I} & 2\mathbf{I} & 4\mathbf{I} & 8\mathbf{I} \dots & 2^{q-1}\mathbf{I} \end{bmatrix} \in \mathbb{R}^{N \times qN}$$

and

$$\mathbf{b} = [\mathbf{b}_1^T \quad \mathbf{b}_2^T \dots \mathbf{b}_q^T]^T \in \mathbb{R}^{qN}$$

with  $\mathbf{b}_i \in \mathbb{R}^N$  for all *i*. Again, both the VA-SDR and BC-SDR problems in this case can be represented by the expression

$$\min_{(\mathbf{S},\mathbf{s})\in\mathcal{F}} \quad f(\mathbf{S},\mathbf{s})$$

where the feasible set  $\mathcal{F}$  for BC-SDR is defined as

$$\mathcal{F}_{\mathsf{BC-SDR}} = \{ (\mathbf{S}, \mathbf{s}) | \mathbf{S} \succeq \mathbf{s} \mathbf{s}^T, \mathbf{1}_N \preceq d(\mathbf{S}) \preceq (2^q - 1)^2 \mathbf{1}_N \}$$
(25)

and the feasible set for VA-SDR is

$$\mathcal{F}_{\mathsf{VA-SDR}} = \left\{ (\mathbf{S}, \mathbf{s}) = (\mathbf{W}\mathbf{B}\mathbf{W}^T, \mathbf{W}\mathbf{b}) | (\mathbf{B}, \mathbf{b}) \in \mathcal{B}_{\mathsf{VA-SDR}} \right\}$$
(26)  
$$\mathcal{B}_{\mathsf{VA-SDR}} = \{ (\mathbf{B}, \mathbf{b}) | \mathbf{B} \succeq \mathbf{b}\mathbf{b}^T, \ d(\mathbf{B}) = \mathbf{1}_{qN} \}.$$

It is shown that the equivalence of BC-SDR and VA-SDR is promised even for higher order QAM.

Theorem 2: Consider a  $4^q$ -QAM constellation, where  $q \ge 1$ . It holds true that

$$\mathcal{F}_{VA-SDR} = \mathcal{F}_{BC-SDR}.$$

The proof of Theorem 2 is given in Appendix B. It is a generalization of its 16-QAM counterpart in Section V-C. Like the 16-QAM case, the proof reveals the possibility that an optimal BC-SDR solution can be used to construct an optimal VA-SDR solution in an analytical fashion, or vice versa.

## B. Equivalence of PI-SDR and BC-SDR for 64-QAM

The original work of PI-SDR [8] concentrates only on the 16-QAM constellation, but it is clear from that work that the idea can be extended to the 64-QAM constellation. To see this, we start with the following 64-QAM ML formulation:

min 
$$||\mathbf{y} - \mathbf{Hs}||^2$$
  
s.t.  $s_i^2 \in \{r_1, r_2, r_3, r_4\}, \quad i = 1, \dots, N$ 

where  $\{r_1, r_2, r_3, r_4\} = \{1, 3^2, 5^2, 7^2\}$ . The idea is to consider the polynomial characterization

$$u \in \{r_1, r_2, r_3, r_4\} \iff \prod_{i=1}^4 (u - r_i) = \sum_{\ell=1}^5 p_\ell u^{\ell-1} = 0$$

where  $\{p_i\}$  is the set of polynomial coefficients associated with the roots  $\{r_i\}$ . Like the development in 16-QAM PI-SDR, we reformulate the ML problem as

$$\min_{\mathbf{U},\mathbf{u},\mathbf{S},\mathbf{s}} f(\mathbf{S},\mathbf{s})$$
s.t. 
$$\mathbf{U} = \begin{bmatrix} \mathbf{U}_{11} & \mathbf{U}_{12} \\ \mathbf{U}_{12}^T & \mathbf{U}_{22} \end{bmatrix}, \quad \mathbf{u} = \begin{bmatrix} \mathbf{u}_1 \\ \mathbf{u}_2 \end{bmatrix}$$

$$\mathbf{S} = \mathbf{s}\mathbf{s}^T, \quad \mathbf{U} = \mathbf{u}\mathbf{u}^T$$

$$d(\mathbf{S}) = \mathbf{u}_1, \quad d(\mathbf{U}_{11}) = \mathbf{u}_2$$

$$p_1 \mathbf{1}_N + p_2 \mathbf{u}_1 + p_3 d(\mathbf{U}_{11}) + p_4 d(\mathbf{U}_{12})$$

$$+ p_5 d(\mathbf{U}_{22}) = \mathbf{0}.$$

$$(28)$$

The formation in (28) is valid because its constraints essentially restrict  $u_i = s_i^2$ ,  $d_i(\mathbf{U}_{11}) = u_i^2$ ,  $d_i(\mathbf{U}_{12}) = u_i^3$ , and  $d_i(\mathbf{U}_{22}) = u_i^4$ . From (28), we obtain the 64-QAM PI-SDR

$$\begin{array}{ll} \min_{\mathbf{U},\mathbf{u},\mathbf{S},\mathbf{s}} & f(\mathbf{S},\mathbf{s}) \\ \text{s.t.} & \mathbf{U} = \begin{bmatrix} \mathbf{U}_{11} & \mathbf{U}_{12} \\ \mathbf{U}_{12}^T & \mathbf{U}_{22} \end{bmatrix}, \quad \mathbf{u} = \begin{bmatrix} \mathbf{u}_1 \\ \mathbf{u}_2 \end{bmatrix} \\ & \mathbf{S} \succeq \mathbf{s} \mathbf{s}^T, \quad \mathbf{U} \succeq \mathbf{u} \mathbf{u}^T \\ & d(\mathbf{S}) = \mathbf{u}_1, \quad d(\mathbf{U}_{11}) = \mathbf{u}_2 \\ & p_1 \mathbf{1}_N + p_2 \mathbf{u}_1 + p_3 d(\mathbf{U}_{11}) + p_4 d(\mathbf{U}_{12}) \\ & + p_5 d(\mathbf{U}_{22}) = \mathbf{0}. \end{array} \tag{29}$$

For BC-SDR, the relaxation is given by

min 
$$f(\mathbf{S}, \mathbf{s})$$
  
s.t.  $\mathbf{S} \succeq \mathbf{s}\mathbf{s}^T$ ,  $r_1 \mathbf{1}_N \preceq d(\mathbf{S}) \preceq r_4 \mathbf{1}_N$ . (30)

The main result here is presented as follows:

Theorem 3: Consider a general situation where the roots  $\{r_i\}$  are allowed to be arbitrary (not necessarily the roots in

64-QAM), and assume  $0 < r_1 < \cdots < r_4 < \infty$ . The PI-SDR problem in (29) and the BC-SDR problem in (30) are equivalent in yielding the same feasible set corresponding to  $(\mathbf{S}, \mathbf{s})$  (and thus the same optimal solutions), under the following sufficient and necessary condition:

$$\sqrt{r_4 - r_1} \le \min\{\sqrt{r_3 - r_1} + \sqrt{r_2 - r_1}, \sqrt{r_4 - r_2} + \sqrt{r_4 - r_3}\}.$$
(31)

It can be verified that the 64-QAM roots  $(\{r_1, r_2, r_3, r_4\} = \{1, 3^2, 5^2, 7^2\})$  satisfy (31). We therefore conclude the following.

Corollary 2: For the 64-QAM constellation, the PI-SDR problem in (29) and the BC-SDR problem in (30) are equivalent in yielding the same feasible set corresponding to  $(\mathbf{S}, \mathbf{s})$ .

*Proof of Theorem 3:* The proof is far from trivial compared to its 16-QAM counterpart. Consider the following lemma shown in Appendix C:

Lemma 2: The PI-SDR problem in (29) is equivalent to the following alternate PI-SDR problem:

$$\begin{array}{ll}
\min_{\mathbf{V}_{1},\dots,\mathbf{V}_{N},\mathbf{S},\mathbf{s}} & f(\mathbf{S},\mathbf{s}) \\
\text{s.t.} & \mathbf{S} \succeq \mathbf{s}\mathbf{s}^{T}, \quad d(\mathbf{S}) = \begin{bmatrix} v_{11},\dots,v_{N,1} \end{bmatrix}^{T} \\
& \mathbf{V}_{i} = \begin{bmatrix} 1 & v_{i1} & v_{i2} \\ v_{i1} & v_{i2} & v_{i3} \\ v_{i2} & v_{i3} & v_{i4} \end{bmatrix} \succeq \mathbf{0}, \quad i = 1,\dots,N \\
& p_{1} + \sum_{\ell=1}^{4} p_{\ell+1}v_{i,\ell} = 0, \quad i = 1,\dots,N
\end{array}$$
(32)

in the sense that the feasible sets corresponding to  $(\mathbf{S}, \mathbf{s})$  are identical for the two problems.

The proof of Lemma 2 follows the same approach as the equivalence proof for the 16-QAM PI-SDR and BC-SDR (in Section V-B). However, by Lemma 2 alone, we are unable to see the equivalence of the 64-QAM PI-SDR and BC-SDR immediately. To gain further insights, let us re-express the alternate PI-SDR formulation in (32) as

min 
$$f(\mathbf{S}, \mathbf{s})$$
  
s.t.  $\mathbf{S} \succeq \mathbf{s} \mathbf{s}^T$ ,  $S_{ii} \in \mathcal{D}$ ,  $i = 1, \dots, N$ 

where we define (33) and (34), shown at the top of the next page, with the operator Hank :  $\mathbb{R}^{2n-1} \rightarrow \mathbb{R}^{n \times n}$  standing for

$$\operatorname{Hank}(a_1, \dots, a_{2n-1}) = \begin{bmatrix} a_1 & a_2 & \dots & a_n \\ a_2 & \ddots & & \vdots \\ \vdots & & \ddots & a_{2n-2} \\ a_n & \dots & a_{2n-2} & a_{2n-1} \end{bmatrix}.$$

Our interest now turns to analyzing the set  $\mathcal{D}$ , which has to be done by analyzing  $\mathcal{V}$ . Consider the following lemma proven in Appendix D:

Authorized licensed use limited to: National Tsing Hua University. Downloaded on January 14, 2010 at 03:51 from IEEE Xplore. Restrictions apply

$$\mathcal{D} = \{ S \in \mathbb{R} | S = [\mathbf{V}]_{12}, \quad \mathbf{V} \in \mathcal{V} \}$$
(33)

$$\mathcal{V} = \left\{ \mathbf{V} \in \mathbb{S}^3 \middle| \mathbf{V} \succeq \mathbf{0}, \quad \mathbf{V} = \operatorname{Hank}((1, \mathbf{v})), \quad p_1 + \sum_{\ell=1}^4 p_{\ell+1} v_\ell = 0, \quad \mathbf{v} \in \mathbb{R}^4 \right\}$$
(34)

Lemma 3: The set  $\mathcal{V}$  in (34) is equivalent to

$$\mathcal{V} = \left\{ \mathbf{V} \in \mathbb{S}^3 \middle| \mathbf{V} = \sum_{\ell=1}^4 \theta_\ell \mathbf{a}_\ell \mathbf{a}_\ell^T, \ \mathbf{V} \succeq \mathbf{0}, \ \sum_{\ell=1}^4 \theta_\ell = 1 \right\} (35)$$

where  $\mathbf{a}_{\ell} = [1, r_{\ell}, r_{\ell}^2]^T$ .

Lemma 3 provides an interesting implication. To describe it, let

$$\operatorname{conv}\{\mathbf{a}_{1}\mathbf{a}_{1}^{T},\ldots,\mathbf{a}_{4}\mathbf{a}_{4}^{T}\} = \left\{ \mathbf{V} \middle| \mathbf{V} = \sum_{\ell=1}^{4} \theta_{\ell} \mathbf{a}_{\ell} \mathbf{a}_{\ell}^{T}, \ \boldsymbol{\theta} \succeq \mathbf{0}, \ \sum_{\ell=1}^{4} \theta_{\ell} = 1 \right\}$$

be the convex hull of  $\{\mathbf{a}_1\mathbf{a}_1^T,\ldots,\mathbf{a}_4\mathbf{a}_4^T\}$ . It can be verified from (35) that  $\mathcal{V} \supseteq \operatorname{conv}\{\mathbf{a}_1\mathbf{a}_1^T,\ldots,\mathbf{a}_4\mathbf{a}_4^T\}$ , though  $\mathcal{V} \subseteq \operatorname{conv}\{\mathbf{a}_1\mathbf{a}_1^T,\ldots,\mathbf{a}_4\mathbf{a}_4^T\}$  is generally not true.<sup>3</sup> Consequently, we have

$$\mathcal{D} \supseteq \{ S = [\mathbf{V}]_{12} | \mathbf{V} \in \operatorname{conv} \{ \mathbf{a}_1 \mathbf{a}_1^T, \dots, \mathbf{a}_4 \mathbf{a}_4^T \} \}$$
$$= \left\{ S = \sum_{\ell=1}^4 \theta_\ell [\mathbf{a}_\ell \mathbf{a}_\ell^T]_{12} \middle| \boldsymbol{\theta} \succeq \mathbf{0}, \sum_{\ell=1}^4 \theta_\ell = 1 \right\}$$
$$= \left\{ S = \sum_{\ell=1}^4 \theta_\ell r_\ell \middle| \boldsymbol{\theta} \succeq \mathbf{0}, \sum_{\ell=1}^4 \theta_\ell = 1 \right\} = [r_1, r_4].$$

This implies that the 64-QAM PI-SDR is no tighter than the 64-QAM BC-SDR, but we also show in Appendix E the following.

Lemma 4: Let  $0 < r_1 < \cdots < r_4 < \infty$ . We have  $\mathcal{D} = [r_1, r_4]$  if and only if

$$\sqrt{r_4 - r_1} \le \min\{\sqrt{r_3 - r_1} + \sqrt{r_2 - r_1}, \sqrt{r_4 - r_2} + \sqrt{r_4 - r_3}\}.$$

As a result, PI-SDR can be equivalent to BC-SDR under the condition in Lemma 4, thereby completing the proof of Theorem 3.

#### C. Numerical Verification of the Equivalence

Simulations were performed to verify the SDR equivalence for the 64-QAM and 256-QAM cases. The simulation settings are the same as those of the 16-QAM simulation example in Section IV, and the MIMO size is  $(\tilde{M}, \tilde{N}) = (4, 4)$ . Simple rounding is employed for the SDR methods. The results are plotted in Fig. 3. We see that the symbol error rates (SERs) of the PI-SDR, BC-SDR, and VA-SDR with simple rounding II are generally identical, which corroborates our theoretical results. It is also noticed that the performance of 64-QAM PI-SDR slightly deviates from that of 64-QAM BC-SDR and

<sup>3</sup>By numerical test, it was found that there exists a  $\mathbf{V} \in \mathcal{V}$  such that some of the constituent  $\theta_{\ell}$  can be negative.



Fig. 3. Comparison of symbol error rates of PI-SDR, BC-SDR, and VA-SDR in a  $4 \times 4$  system with either 64-QAM or 256-QAM.

VA-SDR at SNR= 45dB. We found that this was due to some numerical problems encountered by the interior-point SDP solver (which is SeDuMi [30] here). In fact, the polynomial coefficients in 64-QAM PI-SDR have values ranging from  $p_5 = 1$  to  $p_1 = 1 \times 3^2 \times 5^2 \times 7^2 = 11,025$ . Such a large dynamic range could be the cause of the numerical inaccuracy. Moreover, Fig. 3 illustrates that VA-SDR with simple rounding I is not working in 64-QAM and 256-QAM (see Section IV for the definition of simple roundings I and II). This problem, which has also been noticed by Mao et al. [10], may partially be answered by the equivalence proof for BC-SDR and VA-SDR; cf., Section V-C and Appendix B. In essence, the derivations there revealed that the VA-SDR solution with respect to  $(\mathbf{B}, \mathbf{b})$ may be non-unique, even though its BC-SDR counterpart [in form of (S, s)] is unique. In particular, a key component, namely Lemma 1 is not a unique decomposition.

#### VII. SOME FURTHER SIMULATION RESULTS

We provide two more sets of simulation results to demonstrate the SDR performance compared to some benchmark MIMO detection methods.

#### A. Performance Behaviors in a Generic MIMO Setting

In this simulation example, a comparison is made between SDR and some other MIMO detectors for the 64-QAM case. Again, the simulation setting follows that of the generic MIMO in Section IV. The detectors tested include the zero-forcing (ZF) detector, the optimal sphere decoder, and the lattice reduction aided ZF (LRA-ZF) detector [31], [32]. Note that the LRA-ZF detector has been shown to achieve the full receive diversity

 TABLE I

 AVERAGE COMPUTATIONAL TIME COMPARISON OF BC-SDR AND SPHERE

 DECODING.  $\overline{N} = \overline{M}$ , 64-QAM CONSTELLATION

SNR		Time spent (in sec.)		
		$\tilde{N} = 5$	$\tilde{N} = 10$	$\tilde{N} = 20$
13dB	BC-SDR	0.0050	0.0070	0.0172
	sphere decoder	0.0031	0.0359	54.4323
15dB	BC-SDR	0.0088	0.0070	0.0172
	sphere decoder	0.0031	0.0297	29.0336

[33]. We tested the BC-SDR method only, as the other two SDR methods will provide identical results anyway. The BC-SDR detector was implemented by a specialized interior-point SDP solver developed by the authors [22]. For its solution rounding, we employ the Gaussian randomized rounding described in [8]. The number of randomizations used is 100.

Let us examine the complexities of BC-SDR and sphere decoding. The test was conducted on MATLAB, using a desktop computer with dual 2.66-GHz CPUs. The BC-SDR was written in C mostly, with minor operations using MATLAB. The sphere decoder was also written in C, and the algorithm employed is that of Schnorr–Eucher [15] (which is practically found to be a fast sphere decoder implementation). The result, shown in Table I indicates that sphere decoding yields a better computational advantage than BC-SDR for  $\tilde{N} = 5$ , a small problem size. However, as the problem size increases to  $\tilde{N} = 20$ , the complexity of sphere decoding becomes unaffordable as compared to BC-SDR. As an aside, the sphere decoding complexity behaviors illustrated here confirm the analysis in [17].

In Fig. 4, we compare the symbol error rates of the various MIMO detectors. Fig. 4(a) shows the case of  $\tilde{M} = \tilde{N} = 8$ , where we see that LRA-ZF detector gives better performance than BC-SDR except for some low SNR values. We increase the problem size to  $\tilde{M} = \tilde{N} = 16$  in Fig. 4(b). For this problem size it is computationally too hard to run the optimal sphere decoder. The figure illustrates that for SNRs less than 27 dB, BC-SDR outperforms LRA-ZF. Let us further increase the problem size to  $\tilde{M} = \tilde{N} = 40$ . As illustrated in Fig. 4(c), now BC-SDR exhibits further improved performance compared to LRA-ZF.

The comparisons above suggest that SDR has significant performance advantages for large problem sizes and/or for low to moderate SNRs.

# B. Application to Multiuser MIMO CDMA Systems

We consider a simulation example where SDR and some other MIMO detectors were compared under a uplink multiuser MIMO CDMA scenario [34]. In this scenario, the involvement of multiple users can result in a large problem size. The problem is described as follows. The base station has  $N_r$ receive antennas, while there are K active users, each of which is equipped with  $N_t$  transmit antennas and employs spatial multiplexing to transmit  $N_t$  parallel streams of data. Each user uses a set of  $N_t$  distinct, preassigned spreading code sequences



Fig. 4. Comparison of the various detectors in 64-QAM systems (a)  $(\bar{M}, \bar{N}) = (8, 8)$ . (b)  $(\bar{M}, \bar{N}) = (16, 16)$ . (c)  $(\bar{M}, \bar{N}) = (40, 40)$ .

(with length  $N_c$ ) to send its respective  $N_t$  streams of data. The set of spreading code sequences is also different from one user



Fig. 5. Comparison of the various detectors in a 64-QAM multiuser MIMO CDMA system, with K = 20,  $N_c = 20$ ,  $N_t = 2$  and  $N_r = 2$ .

to another. Under such a setting, the received space-time signal matrix over one symbol interval can be modeled as [34]

$$\mathbf{Y} = \sum_{k=1}^{K} \mathbf{H}_k D(\mathbf{s}_k) \mathbf{C}_k^T + \mathbf{V}$$
(36)

where  $\mathbf{s}_k \in \mathbb{C}^{N_t}$  is the symbol vector transmitted by user k,  $\mathbf{H}_k = [\mathbf{h}_{k,1}, \dots, \mathbf{h}_{k,N_t}] \in \mathbb{C}^{N_r \times N_t}$  is the MIMO channel corresponding to user k,  $\mathbf{C}_k = [\mathbf{c}_{k,1}, \dots, \mathbf{c}_{k,N_t}]$  is the collection of the spreading code sequences of user k, with  $\mathbf{c}_{k,i} \in \mathbb{C}^{N_c}$  being the spreading code sequence for transmit antenna i of user k, and  $\mathbf{V}$  is noise. By vectorization  $\boldsymbol{y} = \text{vec}(\mathbf{Y})$ , it can be shown that the multiuser MIMO model in (36) can be rewritten to a standard form

$$y = Hs + v$$

where  $\boldsymbol{s} = [\mathbf{s}_1^T, \dots, \mathbf{s}_K^T] \in \mathbb{C}^{KN_t}$  is the collection of all symbols to be detected,  $\boldsymbol{H} = [\boldsymbol{H}_1, \dots, \boldsymbol{H}_K] \in \mathbb{C}^{N_c N_r \times KN_t}, \boldsymbol{H}_k = [\mathbf{c}_{k,1} \otimes \mathbf{h}_{k,1}, \dots, \mathbf{c}_{k,N_t} \otimes \mathbf{h}_{k,N_t}] \in \mathbb{C}^{N_c N_r \times N_t}$  ( $\otimes$  denotes the Kronecker product), and  $\boldsymbol{v} = \text{vec}(\mathbf{V})$ .

In the simulation, each channel vector  $\mathbf{h}_{k,i}$  is assumed to be i.i.d. complex circular Gaussian. Moreover, we assume random spreading, where the entries of each  $\mathbf{c}_{k,i}$  have unit magnitude and follow an i.i.d. uniform phase distribution. Fig. 5 displays the simulation results for 64-QAM, K = 20,  $N_c = 20$ ,  $N_t = 2$ and  $N_r = 2$ . It is worthwhile to notice that this setting results in a 40-by-40 64-QAM system. One can see from Fig. 5 that BC-SDR outperforms the other detectors in the test.

# VIII. CONCLUSION AND DISCUSSION

This paper analyzes the relationships of three SDR-based MIMO detection methods for high-order QAM, namely PI-SDR, BC-SDR, and VA-SDR. We have proven that the three SDRs are actually equivalent, despite their different

appearances and complexities. The essence of the equivalence is that an optimal solution of one SDR can always be constructed from that of another SDR. The proof covers general BC-SDR, VA-SDR with any  $4^q$ -QAM ( $q \ge 1$ ), and PI-SDR with 16-QAM and 64-QAM.

Since the three SDRs are now known to be equivalent, the comparison should turn to their computational costs. Our simulation results have shown that BC-SDR is the cheapest computationally, and in parallel a fast specialized interior-point algorithm has been developed to support the implementation of BC-SDR [22]. Hence, it appears that BC-SDR should be the method of choice among the three methods. While this is our present conclusion, our opinion is that each of the three SDRs is interesting in its own right by the different ways they utilize QAM structures. Moreover, the exposition of the PI-SDR and VA-SDR ideas might help inspire future works for devising better SDR methods.

This work also provides several interesting further implications. First, from the analysis one may see that the SDR equivalence result established here does not depend on the objective function. This has enabled us to apply the SDR equivalence result to a rather different problem, namely the blind ML detection of orthogonal space-time block codes [35], [36]. In that parallel investigation, the problem takes on a different objective structure (a Rayleigh quotient function); and the SDR equivalence has proven to be useful in telling which SDR is the most favorable to employ (i.e., BC-SDR).

Second, we should mention the 16-QAM tightened BC-SDR method by Yang *et al.* [11]. Yang *et al.* showed that their tightened BC-SDR method can perform better than the 16-QAM PI-SDR. Using the equivalence result here, we can further infer that the tightened BC-SDR can perform better than the 16-QAM VA-SDR as well.

### APPENDIX

A. Proof of Lemma 1

The proof is constructive. Let

$$\mathbf{u} = \theta \frac{\mathbf{z}}{\|\mathbf{z}\|} + \sqrt{1 - \theta^2} \mathbf{z}_{\perp}$$
(37)

where  $\mathbf{z}_{\perp}$  is a unit 2-norm vector orthogonal to  $\mathbf{z}$ , and  $|\theta| \leq 1$ . It can be verified that the  $\mathbf{u}$  in (37) satisfies  $||\mathbf{u}|| = 1$ . Moreover, let

$$\mathbf{v} = \frac{1}{\beta} (\mathbf{z} - \alpha \mathbf{u}) \tag{38}$$

which is purposely constructed to satisfy  $\mathbf{z} = \alpha \mathbf{u} + \beta \mathbf{v}$ . One can show from (38) that the unit norm condition  $||\mathbf{v}|| = 1$  is achieved when we choose

٦

$$\theta = \frac{\|\mathbf{z}\|^2 - (\beta^2 - \alpha^2)}{2\alpha \|\mathbf{z}\|}.$$
(39)

Now the remaining problem is the condition under which  $|\theta| \le 1$ . It can be verified from (39) that if  $\beta - \alpha \le ||\mathbf{z}|| \le \beta + \alpha$  then  $|\theta| \le 1$  is guaranteed.

# B. Proof of Theorem 2

The idea is similar to the proof in the 16-QAM case, described in Section V-C. We consider two PSD matrices

$$\mathbf{X} = \begin{bmatrix} \mathbf{S} & \mathbf{s} \\ \mathbf{s}^T & 1 \end{bmatrix} \succeq \mathbf{0}, \quad \mathbf{Y} = \begin{bmatrix} \mathbf{B} & \mathbf{b} \\ \mathbf{b}^T & 1 \end{bmatrix} \succeq \mathbf{0}$$

that satisfy  $(\mathbf{S}, \mathbf{b}) = (\mathbf{W}\mathbf{B}\mathbf{W}^T, \mathbf{W}\mathbf{b})$ . That condition is shown to be achievable if

$$\mathbf{Z} = \mathbf{R} \begin{bmatrix} \mathbf{W}^T & \mathbf{0} \\ \mathbf{0} & 1 \end{bmatrix}$$
(40)

where  $\mathbf{Z} \in \mathbb{R}^{(qN+1)\times(N+1)}$  and  $\mathbf{R} \in \mathbb{R}^{(qN+1)\times(qN+1)}$  are square root factors of  $\mathbf{X}$  and  $\mathbf{Y}$ , respectively (or  $\mathbf{Z}^T \mathbf{Z} = \mathbf{X}$ ,  $\mathbf{R}^T \mathbf{R} = \mathbf{Y}$ ). The objective is to show that if  $(\mathbf{S}, \mathbf{s}) \in \mathcal{F}_{\mathsf{BC-SDR}}$ , then we can construct a  $(\mathbf{B}, \mathbf{b}) \in \mathcal{B}_{\mathsf{VA-SDR}}$  satisfying (40); and vice versa.

For general  $4^{q}$ -QAM where **W** is expanded to  $[\mathbf{I} \ 2\mathbf{I} \dots 2^{q-1}\mathbf{I}], (40)$  can be rewritten as

$$\mathbf{z}_{i} = \sum_{i=0}^{q-1} 2^{j} \mathbf{r}_{i+jN}, \quad i = 1, \dots, N$$
 (41)

$$\mathbf{z}_{N+1} = \mathbf{r}_{qN+1}.\tag{42}$$

To achieve (42) is easy, and the nontrivial part lies in (41). First, suppose  $(\mathbf{B}, \mathbf{b}) \in \mathcal{B}_{VA-SDR}$ . Then the resultant  $\mathbf{R}$  satisfies  $||\mathbf{r}_i|| = 1$ . The vectors  $\mathbf{z}_i$  satisfying (41) would then have bounds

$$\begin{aligned} \|\mathbf{z}_{i}\| &\leq \sum_{j=0}^{q-1} 2^{j} \|\mathbf{r}_{i+jN}\| = \sum_{j=0}^{q-1} 2^{j} = 2^{q} - 1 \\ \|\mathbf{z}_{i}\| &\geq 2^{q-1} \|\mathbf{r}_{i+(q-1)N}\| - \left\|\sum_{j=0}^{q-2} 2^{j} \mathbf{r}_{i+jN}\right\| \\ &\geq 2^{q-1} - \sum_{j=0}^{q-2} 2^{j} = 2^{q-1} - (2^{q-1} - 1) = 1. \end{aligned}$$

This means that the corresponding **S** has  $d_i(\mathbf{S}) = ||\mathbf{z}_i||^2 \in [1, (2^q - 1)^2]$ . Hence,  $(\mathbf{S}, \mathbf{s}) \in \mathcal{F}_{\mathsf{BC-SDR}}$ . Second, suppose  $(\mathbf{S}, \mathbf{s}) \in \mathcal{B}_{\mathsf{BC-SDR}}$ . Let us choose, for each  $i = 1, \ldots, N$ ,

$$\mathbf{r}_{i} = \mathbf{r}_{i+N} = \dots = \mathbf{r}_{i+(q-2)N} \triangleq \mathbf{u}_{i}$$
$$\mathbf{r}_{i+(q-1)N} \triangleq \mathbf{v}_{i}$$

for some  $\mathbf{u}_i, \mathbf{v}_i \in \mathbb{R}^{qN+1}$ . The condition in (41) becomes

$$\mathbf{z}_{i} = \sum_{j=0}^{q-2} 2^{j} \mathbf{u}_{i} + 2^{q-1} \mathbf{v}_{i} = (2^{q-1} - 1) \mathbf{u}_{i} + 2^{q-1} \mathbf{v}_{i}.$$
 (43)

Using Lemma 1, we can construct a  $(\mathbf{u}_i, \mathbf{v}_i)$  that satisfies (43) for any  $\|\mathbf{z}_i\| = \sqrt{d_i(\mathbf{S})} \in [1, 2^q - 1]$  while achieving  $\|\mathbf{u}_i\| = \|\mathbf{v}_i\| = 1$ . The resultant **B** will therefore satisfy  $d_i(\mathbf{B}) = Y_{ii} = 1$  for all *i*, meaning that  $(\mathbf{B}, \mathbf{b}) \in \mathcal{B}_{VA-SDR}$ .

The proof of Theorem 2 is complete.

# C. Proof of Lemma 2

Suppose that  $(\mathbf{U}, \mathbf{u}, \mathbf{S}, \mathbf{s})$  is feasible to the original 64-QAM PI-SDR problem in (29). Set

$$\mathbf{V}_{i} = \begin{bmatrix} 1 & \mathbf{0} \\ 0 & \mathbf{e}_{i}^{T} \\ 0 & \mathbf{e}_{i+N}^{T} \end{bmatrix} \begin{bmatrix} 1 & \mathbf{u}^{T} \\ \mathbf{u} & \mathbf{U} \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 \\ \mathbf{0} & \mathbf{e}_{i} & \mathbf{e}_{i+N} \end{bmatrix}$$
(44)

for i = 1, ..., N, where  $\mathbf{e}_i \in \mathbb{R}^{2N}$  is a unit vector with the nonzero element at the *i*th element. It follows from  $\mathbf{U} \succeq \mathbf{u}\mathbf{u}^T$  and (44) that  $\mathbf{V}_i \succeq \mathbf{0}$  for all *i*. Moreover, (44) equals

$$\mathbf{V}_{i} = \begin{bmatrix} 1 & u_{1i} & u_{2i} \\ u_{1i} & [\mathbf{U}_{11}]_{ii} & [\mathbf{U}_{12}]_{ii} \\ u_{2i} & [\mathbf{U}_{12}]_{ii} & [\mathbf{U}_{22}]_{ii} \end{bmatrix}.$$
 (45)

Since  $u_{2i} = [\mathbf{U}_{11}]_{ii}$ , every  $\mathbf{V}_i$  in (45) satisfies the Hankel structure in the alternate PI-SDR problem in (32). It also follows from (45) that the equality constraints arising from the polynomials are satisfied. Hence,  $(\mathbf{V}_1, \dots, \mathbf{V}_N, \mathbf{S}, \mathbf{s})$  is feasible to the alternate PI-SDR problem in (32).

On the other hand, suppose that  $(V_1, \ldots, V_N, S, s)$  is feasible to the alternate PI-SDR. Set

$$\mathbf{u}_1 = [v_{11}, \dots, v_{N,1}]^T$$
 (46a)

$$\mathbf{U}_{11} = \mathbf{C}_2 - D(\mathbf{u}_1 \odot \mathbf{u}_1) + \mathbf{u}_1 \mathbf{u}_1^T$$
(46b)

$$\mathbf{u}_2 = d(\mathbf{U}_{11}) = [v_{12}, \dots, v_{N,2}]^T$$
 (46c)

$$\mathbf{U}_{12} = \mathbf{C}_3 - D(\mathbf{u}_1 \odot \mathbf{u}_2) + \mathbf{u}_1 \mathbf{u}_2^T$$
(46d)

$$\mathbf{U}_{22} = \mathbf{C}_4 - D(\mathbf{u}_2 \odot \mathbf{u}_2) + \mathbf{u}_2 \mathbf{u}_2^T$$
(46e)

where  $\odot$  is the Hadamard product, and

$$\mathbf{C}_i = D(v_{1,i},\ldots,v_{N,i}).$$

It can be shown that (46) satisfies the equality constraints of the polynomials. Let us examine if  $\mathbf{U} \succeq \mathbf{u}\mathbf{u}^T$ . We see that

$$\mathbf{U} - \mathbf{u}\mathbf{u}^{T} = \begin{bmatrix} \mathbf{C}_{2} - D(\mathbf{u}_{1} \odot \mathbf{u}_{1}) & \mathbf{C}_{3} - D(\mathbf{u}_{1} \odot \mathbf{u}_{2}) \\ \mathbf{C}_{3} - D(\mathbf{u}_{1} \odot \mathbf{u}_{2}) & \mathbf{C}_{4} - D(\mathbf{u}_{2} \odot \mathbf{u}_{2}) \end{bmatrix}.$$

It can be shown using basic matrix results that the specially structured matrix above is PSD if and only if

$$\begin{bmatrix} v_{i,2} - u_{1,i}^2 & v_{i,3} - u_{1,i}u_{2,i} \\ v_{i,3} - u_{1,i}u_{2,i} & v_{i,4} - u_{2,i}^2 \end{bmatrix}$$
(47)

are PSD for all i = 1, ..., N. By using  $u_{1,i} = v_{i,1}$  and  $u_{2,i} = v_{i,2}$  and Schur complement, it is shown that (47) is indeed PSD. We therefore conclude that  $(\mathbf{V}_1, ..., \mathbf{V}_N, \mathbf{S}, \mathbf{s})$  is feasible to the alternate PI-SDR problem.

## D. Proof of Lemma 3

Consider a problem setting as follows. Let  $\{r_1, \ldots, r_L\}$  be a given set of roots, and assume that the roots are distinct. Consider the following two sets

$$\mathcal{V}_1 = \left\{ \mathbf{V} = \operatorname{Hank}(\mathbf{v}) \middle| \mathbf{v} \in \mathbb{R}^{L+1}, v_1 = 1, \mathbf{p}^T \mathbf{v} = 0, \mathbf{V} \succeq \mathbf{0} \right\}$$

Authorized licensed use limited to: National Tsing Hua University. Downloaded on January 14, 2010 at 03:51 from IEEE Xplore. Restrictions apply

where  $\mathbf{p} = [p_1, \ldots, p_{L+1}]^T$  contains the polynomial coefficients corresponding to  $\{r_1, \ldots, r_L\}$ , i.e.,  $\sum_{\ell=1}^{L+1} p_\ell r^{\ell-1} = 0$  for all  $r \in \{r_1, \ldots, r_L\}$ ; and

$$\mathcal{V}_2 = \left\{ \mathbf{V} = \sum_{\ell=1}^{L} \theta_\ell \mathbf{a}_\ell \mathbf{a}_\ell^T \middle| \sum_{\ell=1}^{L} \theta_\ell = 1, \ \mathbf{V} \succeq \mathbf{0} \right\}$$

where  $\mathbf{a}_{\ell} = [1, r_{\ell}, r_{\ell}^2, \dots, r_{\ell}^{L/2}]^T \in \mathbb{R}^{L/2+1}$ , and L is assumed to be even. Our objective is to prove that  $\mathcal{V}_1 = \mathcal{V}_2$ . Clearly, Lemma 3 is a special case of the above problem where L = 4.

By definition, every  $\mathbf{V} \in \mathcal{V}_1$  can be parameterized by some  $\mathbf{v} \in \mathbb{R}^{L+1}$  such that  $v_1 = 1$  and  $\mathbf{p}^T \mathbf{v} = 0$ . Let

$$\mathbf{b}_{\ell} = [1, r_{\ell}, r_{\ell}^2, \dots, r_{\ell}^L]^T \in \mathbb{R}^{L+1}$$

for  $\ell = 1, ..., L$ . Since every  $\mathbf{b}_{\ell}$  contains one of the true roots, it satisfies  $\mathbf{p}^T \mathbf{b}_{\ell} = 0$ . Hence, we have the following condition to satisfy

$$\mathbf{p}^T[\mathbf{b}_1 \dots \mathbf{b}_L \mathbf{v}] = \mathbf{0}. \tag{48}$$

The submatrix  $[\mathbf{b}_1 \dots \mathbf{b}_L] \in \mathbb{R}^{(L+1) \times L}$  is linearly independent, *L* being Vandemonde with distinct roots. Subsequently, (48) can be satisfied only when

$$\mathbf{v} = \sum_{\ell=1}^{L} \theta_{\ell} \mathbf{b}_{\ell}.$$

for some coefficients  $\boldsymbol{\theta} \in \mathbb{R}^L$ . Since  $1 = v_1 = \sum_{\ell=1}^L \theta_\ell [\mathbf{b}_\ell]_1 = \sum_{\ell=1}^L \theta_\ell$ , the coefficients satisfy  $\sum_{\ell=1}^L \theta_\ell = 1$ . Moreover, by noticing that

$$\operatorname{Hank}(\mathbf{b}_{\ell}) = \mathbf{a}_{\ell} \mathbf{a}_{\ell}^{T}$$
(49)

we have

$$\mathbf{V} = \mathrm{Hank}(\mathbf{v}) = \sum_{\ell=1}^{L} \theta_{\ell} \mathbf{a}_{\ell} \mathbf{a}_{\ell}^{T}.$$

Hence, any  $\mathbf{V} \in \mathcal{V}_1$  lies in  $\mathcal{V}_2$ .

Likewise, it can be verified that every  $\mathbf{V} \in \mathcal{V}_2$  lies in  $\mathcal{V}_1$ : For every  $\mathbf{V} \in \mathcal{V}_2$  which can be characterized as  $\mathbf{V} = \sum_{\ell=1}^{L} \theta_\ell \mathbf{a}_\ell \mathbf{a}_\ell^T, \sum_{\ell=1}^{L} \theta_\ell = 1$ , set

$$\mathbf{v} = \sum_{\ell=1}^{L} \theta_{\ell} \mathbf{b}_{\ell}.$$

It follows from (49) that  $\operatorname{Hank}(\mathbf{v}) = \mathbf{V}$ . Moreover, this  $\mathbf{v}$  satisfies  $v_1 = \sum_{\ell=1}^{L} \theta_\ell [\mathbf{b}_\ell]_1 = 1$ , and  $\mathbf{p}^T \mathbf{v} = \sum_{\ell=1}^{L} \theta_\ell \mathbf{p}^T \mathbf{b}_\ell = 0$ .

E. Proof of Lemma 4

By Lemma 3, the set  $\mathcal{D}$  can be expressed as

$$\mathcal{D} = \left\{ S = \sum_{\ell=1}^{4} \theta_{\ell} r_{\ell} \middle| \sum_{\ell=1}^{4} \theta_{\ell} \mathbf{a}_{\ell} \mathbf{a}_{\ell}^{T} \succeq \mathbf{0}, \sum_{\ell=1}^{4} \theta_{\ell} = 1 \right\}.$$

This set is a closed convex set, and therefore must be in form of an interval [L, U]. The proof is divided into three parts: solving L, solving U, and integrating the results.

Solving the Lower Bound: We find the lower bound L by solving the problem

$$L = \min_{\boldsymbol{\theta}} \quad \sum_{\ell=1}^{4} \theta_{\ell} r_{\ell}$$
  
s.t. 
$$\sum_{\ell=1}^{4} \theta_{\ell} \mathbf{a}_{\ell} \mathbf{a}_{\ell}^{T} \succeq \mathbf{0}, \quad \sum_{\ell=1}^{4} \theta = 1.$$
(50)

Let  $x_i = \theta_{i+1}$ , i = 1, 2, 3. Using  $\theta_1 = 1 - \sum_{i=1}^3 x_i$ , Problem (50) can be re-expressed as

$$L = \min_{\mathbf{x}} \quad r_1 + \sum_{i=1}^{3} x_i (r_{i+1} - r_1)$$
  
s.t.  $\mathbf{a}_1 \mathbf{a}_1^T + \sum_{i=1}^{3} x_i (\mathbf{a}_{i+1} \mathbf{a}_{i+1}^T - \mathbf{a}_1 \mathbf{a}_1^T) \succeq \mathbf{0}.$  (51)

By strong duality, solving (51) is the same as solving its dual which can be shown to be

$$L = \max_{\mathbf{Z} \in \mathbb{S}^3} \quad r_1 - \operatorname{tr}(\mathbf{a}_1 \mathbf{a}_1^T \mathbf{Z})$$
  
s.t.  $\mathbf{Z} \succeq \mathbf{0},$   
 $\operatorname{tr}[(\mathbf{a}_1 \mathbf{a}_1^T - \mathbf{a}_{i+1} \mathbf{a}_{i+1}^T)\mathbf{Z}] = r_1 - r_{i+1}, \quad i = 1, 2, 3.$   
(52)

From the objective in (52), it is clear that  $L = r_1$  if and only if **Z** is feasible and satisfies

$$\operatorname{tr}(\mathbf{a}_1 \mathbf{a}_1^T \mathbf{Z}) = 0. \tag{53}$$

Let us consider the construction of a PSD Z satisfying (53). Equation (53) implies that Z has rank no greater than 2. Thus any such PSD Z can be represented by

$$\mathbf{Z} = \mathbf{R}\mathbf{R}^T$$

where  $\mathbf{R} \in \mathbb{R}^{3 \times 2}$  is such that  $\mathbf{R}^T \mathbf{a}_1 = \mathbf{0}$ . Such an  $\mathbf{R}$  can be parameterized as

$$\mathbf{R} = [\mathbf{W}\boldsymbol{\alpha}_1, \, \mathbf{W}\boldsymbol{\alpha}_2]$$

for some  $\boldsymbol{\alpha}_1, \boldsymbol{\alpha}_2 \in \mathbb{R}^2$ , where

$$\mathbf{W} = \begin{bmatrix} 1 & 1\\ \frac{-1}{r_1} & \frac{-2}{r_1}\\ 0 & \frac{1}{r_1^2} \end{bmatrix}.$$

(One can easily check that  $\mathbf{a}_1^T \mathbf{W} = \mathbf{0}$ , thereby  $\mathbf{R}^T \mathbf{a}_1 = \mathbf{0}$ .) Therefore, any PSD Z satisfying (53) can be expressed as

$$\mathbf{Z} = \mathbf{W}\mathbf{G}\mathbf{W}^T \tag{54}$$

where

$$\mathbf{G} = \begin{bmatrix} a & b \\ b & c \end{bmatrix} = \begin{bmatrix} \boldsymbol{\alpha}_1 & \boldsymbol{\alpha}_2 \end{bmatrix} \begin{bmatrix} \boldsymbol{\alpha}_1^T \\ \boldsymbol{\alpha}_2^T \end{bmatrix} \succeq \mathbf{0}$$

can be any  $2 \times 2$  PSD matrix.

By substituting the matrix form in (54) into the equality constraints in (52), we obtain

$$\mathbf{a}_{i+1}^T \mathbf{W} \mathbf{G} \mathbf{W}^T \mathbf{a}_{i+1} = r_{i+1} - r_1, \quad i = 1, 2, 3.$$
 (55)

We seek to find the sufficient and necessary conditions for satisfying (55). By noticing that

$$\mathbf{W}^{T}\mathbf{a}_{i+1} = \begin{bmatrix} 1 & \frac{-1}{r_{1}} & 0\\ 1 & \frac{-2}{r_{1}} & \frac{1}{r_{1}^{2}} \end{bmatrix} \begin{bmatrix} 1\\ r_{i+1}\\ r_{i+1}^{2} \end{bmatrix}$$
$$= \begin{bmatrix} \frac{1-r_{i+1}}{r_{1}}\\ \left(\frac{1-r_{i+1}}{r_{1}}\right)^{2} \end{bmatrix}.$$

Equation (55) can be decomposed to

$$r_1 - a\left(\frac{r_{i+1}}{r_1} - 1\right) + 2b\left(\frac{r_{i+1}}{r_1} - 1\right)^2 - c\left(\frac{r_{i+1}}{r_1} - 1\right)^3 = 0$$
(56)

for i = 1, 2, 3. Let us define a polynomial function

$$f(u) = r_1 - au + 2bu^2 - cu^3$$

Since the function satisfies  $f(r_{i+1}/r_1 - 1) = 0$  for i = 1, 2, 3 [cf., (56)], it permits a factored form

$$f(u) = r_1 \prod_{j=1}^3 \left(1 - \frac{u}{u_j}\right)$$

where

$$u_j = \frac{r_{j+1}}{r_1} - 1 > 0$$

By expanding the factored form of f(u) to the polynomial form, we determine (rather tediously) that

$$\begin{split} a &= \frac{r_1}{u_1 u_2 u_3} (u_1 u_2 + u_2 u_3 + u_1 u_3) > 0 \\ b &= \frac{r_1}{2 u_1 u_2 u_3} (u_1 + u_2 + u_3) > 0 \\ c &= \frac{r_1}{u_1 u_2 u_3} > 0. \end{split}$$

The remaining part lies in ensuring that the resultant G is PSD. We already have a > 0 and c > 0, so the last condition is  $b^2 - ac \le 0$  by Schur complement. With some cumbersome derivations, we show that

$$b^{2} - ac = \left(\frac{r_{1}}{2u_{1}u_{2}u_{3}}\right)^{2} [u_{3} - (\sqrt{u_{1}} - \sqrt{u_{2}})^{2}] \times [u_{3} - (\sqrt{u_{1}} + \sqrt{u_{2}})^{2}]$$

In order to achieve  $b^2 - ac \leq 0$ , we need

$$(\sqrt{u_1} - \sqrt{u_2})^2 \le u_3 \le (\sqrt{u_1} + \sqrt{u_2})^2.$$
(57)

Summarizing, we have  $L = r_1$  if and only if (57) holds.

Solving the Upper Bound: The method of the proof is exactly the same as the previous, and hence the detailed derivations are omitted for brevity. Essentially, we consider solving the upper bound

$$U = \max_{\boldsymbol{\theta}} \quad \sum_{i=1}^{4} \theta_i r_i$$
  
s.t. 
$$\sum_{i=1}^{4} \theta_i \mathbf{a}_i \mathbf{a}_i^T \succeq \mathbf{0}, \ \sum_{i=1}^{4} \theta_i = 1$$

by solving its dual

$$U = \min_{\mathbf{Z} \in \mathbb{S}^3} \quad r_4 + \operatorname{tr}(\mathbf{a}_4 \mathbf{a}_4^T \mathbf{Z})$$
  
s.t.  $\mathbf{Z} \succeq \mathbf{0},$   
 $\operatorname{tr}[(\mathbf{a}_4 \mathbf{a}_4^T - \mathbf{a}_i \mathbf{a}_i^T)\mathbf{Z}] = r_i - r_4, \quad i = 1, 2, 3.$ (58)

From (58) it is shown that  $U = r_4$  if and only if

$$(\sqrt{v_2} - \sqrt{v_3})^2 \le v_1 \le (\sqrt{v_2} + \sqrt{v_3})^2.$$
 (59)

where  $v_i = 1 - r_i/r_4 > 0$  for i = 1, 2, 3.

*Combining the Conditions:* The final task is to combine the conditions in (57) and (59). We can express (57) as

$$\sqrt{r_3 - r_1} - \sqrt{r_2 - r_1} \le \sqrt{r_4 - r_1} \le \sqrt{r_3 - r_1} + \sqrt{r_2 - r_1}.$$

The lower bound is redundant because for any  $r_4 > \cdots > r_1 > 0$ ,

$$\sqrt{r_4 - r_1} \ge \sqrt{r_3 - r_1} \ge \sqrt{r_3 - r_1} - \sqrt{r_2 - r_1}.$$

Moreover, (59) can be expressed as

$$\sqrt{r_4 - r_2} - \sqrt{r_4 - r_3} \le \sqrt{r_4 - r_1} \le \sqrt{r_4 - r_2} + \sqrt{r_4 - r_3}$$

and again the lower bound can be shown to be automatically satisfied. We therefore obtain the sufficient and necessary condition in Lemma 4, completing the proof.

#### REFERENCES

- P. Tan and L. Rasmussen, "The application of semidefinite programming for detection in CDMA," *IEEE J. Select. Areas Commun.*, vol. 19, no. 4, pp. 1442–1449, Apr. 2001.
- [2] W.-K. Ma, T. N. Davidson, K. M. Wong, Z.-Q. Luo, and P. C. Ching, "Quasi-maximum-likelihood multiuser detection using semi-definite relaxation with application to synchronous CDMA," *IEEE Trans. Signal Process.*, vol. 50, no. 4, pp. 912–922, Apr. 2002.
- [3] W.-K. Ma, P. C. Ching, and Z. Ding, "Semidefinite relaxation based multiuser detection for M-ary PSK multiuser systems," *IEEE Trans. Signal Process.*, vol. 52, no. 10, pp. 2862–2872, Oct. 2004.
- [4] M. Abdi, H. E. Nahas, A. Jard, and E. Moulines, "Semidefinite positive relaxation of the maximum-likelihood criterion applied to multiuser detection in a CDMA context," *IEEE Signal Process. Lett.*, vol. 9, no. 6, pp. 165–167, Jun. 2002.
- [5] X. M. Wang, W.-S. Lu, and A. Antoniou, "A near-optimal multiuser detector for DS-CDMA systems using semidefinite programming relaxation," *IEEE Trans. Signal Process.*, vol. 51, no. 9, pp. 2446–2450, Sep. 2003.

Authorized licensed use limited to: National Tsing Hua University. Downloaded on January 14, 2010 at 03:51 from IEEE Xplore. Restrictions apply.

- [6] W.-K. Ma, T.-N. Davidson, K. M. Wong, and P. C. Ching, "A block alternating likelihood maximization approach to multiuser detection," *IEEE Trans. Signal Process.*, vol. 52, no. 9, pp. 2600–2611, Sep. 2004.
- [7] B. Steingrimsson, Z.-Q. Luo, and K. M. Wong, "Soft quasi-maximum-likelihood detection for multiple-antenna wireless channels," *IEEE Trans. Signal Process.*, vol. 51, no. 11, pp. 2710–2719, Nov. 2003.
- [8] A. Wiesel, Y. C. Eldar, and S. Shamai, "Semidefinite relaxation for detection of 16-QAM signaling in MIMO channels," *IEEE Signal Process. Lett.*, vol. 12, no. 9, pp. 653–656, Nov. 2005.
- [9] N. D. Sidiropoulos and Z.-Q. Luo, "A semidefinite relaxation approach to MIMO detection for higher-order constellations," *IEEE Signal Process. Lett.*, vol. 13, no. 9, pp. 525–528, Sep. 2006.
- [10] Z. Mao, X. Wang, and X. Wang, "Semidefinite programming relaxation approach for multiuser detection of QAM signals," *IEEE Trans. Wireless Commun.*, vol. 6, no. 12, pp. 4275–4279, Dec. 2007.
- [11] Y. Yang, C. Zhao, P. Zhou, and W. Xu, "MIMO detection of 16-QAM signaling based on semidefinite relaxation," *IEEE Signal Process. Lett.*, vol. 14, no. 11, pp. 797–800, Nov. 2007.
- [12] A. Mobasher, M. Taherzadeh, R. Sotirov, and A. K. Khandani, "A nearmaximum-likelihood decoding algorithm for MIMO systems based on semi-definite programming," *IEEE Trans. Inf. Theory*, vol. 53, no. 11, pp. 3869–3886, Nov. 2007.
- [13] J. Jaldén and B. Ottersten, "The diversity order of the semidefinite relaxation detector," *IEEE Trans. Inf. Theory*, vol. 54, no. 4, pp. 1406–1422, Apr. 2008.
- [14] M. Kisialiou and Z.-Q. Luo, "Performance analysis of quasi-maximum-likelihood detector based on semi-definite programming," in *Proc. IEEE Int. Conf. Acoustics, Speech, Signal Process.*, Philadelphia, PA, Mar. 2005, pp. 433–436.
- [15] M. O. Damen, H. E. Gamal, and G. Caire, "On maximum-likelihood detection and the search for the closest lattice point," *IEEE Trans. Inf. Theory*, vol. 49, no. 10, pp. 2389–2402, Oct. 2003.
- [16] A. D. Murugan, H. E. Gamal, M. O. Damen, and G. Caire, "A unified framework for tree search decoding: Rediscovering the sequential decoder," *IEEE Trans. Inf. Theory*, vol. 52, no. 3, pp. 933–953, Mar. 2006.
- [17] J. Jaldén and B. Ottersten, "On the complexity of sphere decoding in digital communications," *IEEE Trans. Signal Process.*, vol. 53, no. 4, pp. 1474–1484, Apr. 2005.
- [18] L. G. Barbero and J. S. Thompson, "Performance analysis of a fixed-complexity sphere decoder in high-dimensional MIMO systems," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process.*, Toulouse, France, May 2006, vol. 4, pp. 557–560.
- [19] J. Jaldén, B. Ottersten, and W.-K. Ma, "Reducing the average complexity of ML detection using semidefinite relaxation," in *Proc. IEEE Int. Conf. Acousti., Speech, Signal Process.*, Philadelphia, PA, Mar. 2005, pp. 1021–1024.
- [20] M. Kisialiou and Z.-Q. Luo, "Efficient implementation of a quasi-maximum-likelihood detector based on semi-definite relaxation," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process.*, Honolulu, Hawaii, Apr. 2007, pp. 1329–1332 [Online]. Available: http://www.ece.umn. edu/users/luozq/software/sw\_about.html
- [21] M. Nekuii, M. Kisialiou, T. N. Davidson, and Z.-Q. Luo, "Efficient soft demodulation of MIMO QPSK via semidefinite relxation," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process.*, Las Vegas, NV, Mar. 2008, pp. 2665–2668.
- [22] W.-K. Ma, C.-C. Su, J. Jaldén, and C.-Y. Chi, "Some results on 16-QAM MIMO detection using semidefinite relaxation," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process.*, Las Vegas, NV, Apr. 2008, pp. 2673–2676.
- [23] G. D. Golden, C. J. Foschini, R. A. Valenzuela, and P. W. Wolniansky, "Detection algorithm and initial laboratory results using V-BLAST space-time communication architecture," *Electron. Lett.*, vol. 35, no. 1, pp. 14–16, 1999.
- [24] D. Tse and P. Viswanath, *Fundamentals of Wireless Communication*. Cambridge, U.K.: Cambridge Univ. Press, 2005.
- [25] S. Verdú, Multiuser Detection. Cambridge, U.K.: Cambridge Univ. Press, 1998.
- [26] B. Hassibi and M. Hochward, "High-rate codes that are linear in space and time," *IEEE Trans. Inf. Theory*, vol. 48, no. 7, pp. 1804–1824, Jul. 2002.

- [27] W. Su, Z. Safar, and K. J. R. Liu, "Full-rate full-diversity space-frequency codes with optimum coding advantages," *IEEE Trans. Inf. Theory*, vol. 51, no. 1, pp. 229–249, Jan. 2005.
- [28] L. Vandenberghe and S. Boyd, "Semidefinite programming," SIAM Rev., vol. 38, no. 1, pp. 49–95, 1996.
- [29] C. Helmberg, F. Rendl, R. Vanderbei, and H. Wolkowicz, "An interiorpoint method for semidefinite programming," *SIAM J. Optim.*, vol. 6, no. 2, pp. 342–361, 1996.
- [30] J. F. Sturm, "Using SeDuMi 1.02, a MATLAB toolbox for optimization over symmetric cones," *Optimization Methods and Software*, vol. 11–12, pp. 625–653, 1999.
- [31] H. Yao and G. W. Wornell, "Lattice-reduction-aided detectors for MIMO communication systems," in *Proc. 2002 IEEE Global Telecomm. Conf.*, Taipei, Taiwan, Nov. 2002, vol. 1, pp. 424–428.
- [32] Y. H. Gan and W. H. Mow, "Complex lattice reduction algorithm for low-complexity MIMO detection," in *Proc. IEEE Global Telecomm. Conf.*, St. Louis, MO, Dec. 2005, pp. 2953–2957.
- [33] M. Taherzadeh, A. Mobasher, and A. K. Khandani, "LLL reduction achieves the receive diversity in MIMO decoding," *IEEE Trans. Inf. Theory*, vol. 53, no. 12, pp. 4801–4805, Dec. 2007.
- [34] A. Nordio and G. Taricco, "Linear receivers for the multiple-input multiple-output multiple-access channel," *IEEE Trans. Commun.*, vol. 54, no. 8, pp. 1446–1456, Aug. 2006.
- [35] C.-W. Hsin, T.-H. Chang, W.-K. Ma, and C.-Y. Chi, "A linear fractional semidefinite relaxed ML approach to blind detection of 16-QAM orthogonal space-time block codes," in *Proc. IEEE Int. Conf. Commun.*, Beijing, China, May 2008, pp. 790–794.
- [36] T.-H. Chang, C.-W. Hsin, W.-K. Ma, and C.-Y. Chi, "A linear fractional semidefinite relaxation approach to maximum-likelihood detection of higher-order QAM OSTBC in unknown channels," *IEEE Trans. Signal Process.*, 2010, to be published.



Wing-Kin Ma (S'96–M'01) received the B.Eng. (first-class hons.) degree in electrical and electronic engineering from the University of Portsmouth, Portsmouth, U.K., in 1995 and the M.Phil. and Ph.D. degrees, both in electronic engineering, from the Chinese University of Hong Kong (CUHK), Hong Kong, in 1997 and 2001, respectively.

He is currently an Assistant Professor in the Department of Electronic Engineering, CUHK. From 2005 to 2007, he was also an Assistant Professor with the Institute of Communications Engineering,

National Tsing Hua University, Hsinchu, Taiwan, where he is still holding an adjunct position. Prior to becoming a faculty member, he held various research positions at McMaster University, Hamilton, ON, Canada; CUHK, Hong Kong; and the University of Melbourne, Melbourne, Australia. His research interests are in signal processing and communications, with a recent emphasis on MIMO techniques and convex optimization.

Dr. Ma's Ph.D. dissertation was commended to be "of very high quality and well deserved honorary mentioning" by the Faculty of Engineering, CUHK, in 2001. He currently serves as Associate Editors of the IEEE TRANSACTIONS ON SIGNAL PROCESSING and the IEEE SIGNAL PROCESSING LETTERS. He is also a Guest Editor of the *IEEE Signal Processing Magazine*, Special Issue on "Convex Optimization for Signal Processing."



**Chao-Cheng Su** received the B.S. degree in mathematics and the M.S. degree in communications engineering from the National Tsing Hua University, Hsinchu, Taiwan, in 2006 and 2008, respectively.

Since September 2008, he has been with Sunplus, Inc., Hsinchu, where he works on algorithm design for digital video broadcasting. His research interests include digital signal processing and wireless communications.



**Joakim Jaldén** received the M.Sc. and Ph.D. in electrical engineering from the Royal Institute of Technology (KTH), Stockholm, Sweden, in 2002 and 2007, respectively.

From September 2000 to May 2002, he studied at Stanford University, Stanford, CA. From July 2007 to June 2009, he was at the Vienna University of Technology, Vienna, Austria, as a Post-Doctoral Researcher. In July 2009, he joined the Signal Processing Lab within the School of Electrical Engineering, KTH, as an Assistant Professor.

Dr. Jaldén was awarded the IEEE Signal Processing (SP) Society's 2006 Young Author Best Paper Award and the first prize in the Student Paper Contest at the 2007 International Conference on Acoustics, Speech, and Signal Processing (ICASSP) for his work on MIMO communications. His Ph.D. position at KTH was funded by a grant, "Honor Graduate Student Position," awarded by the dean office.



**Tsung-Hui Chang** (S'07–M'08) received the B.S. degree in electrical engineering and the Ph.D. degree in communications engineering from the National Tsing Hua University (NTHU), Hsinchu, Taiwan, in 2003 and 2008, respectively. From September 2006 to February 2008, he was an exchange Ph.D. student at the University of Minnesota, Minneapolis.

Currently, he is a Post-Doctoral Research Fellow with the Institute of Communications Engineering, NTHU. His research interests are widely in wireless communications, digital signal processing, and

convex optimization and its applications.



**Chong-Yung Chi** (S'83–M'83–SM'89) received the Ph.D. degree in electrical engineering from the University of Southern California, Los Angeles, in 1983.

From 1983 to 1988, he was with the Jet Propulsion Laboratory, Pasadena, CA. He has been a Professor with the Department of Electrical Engineering since 1989 and the Institute of Communications Engineering (ICE) since 1999 (also the Chairman of ICE for 2002–2005), National Tsing Hua University, Hsinchu, Taiwan. He coauthored a technical book, Blind Equalization and System Identification

(Springer, 2006) and published more than 150 technical (journal and conference) papers. His current research interests include signal processing for wireless communications, convex analysis and optimization for blind source separation, biomedical imaging, and hyperspectral imaging.

Dr. Chi has been a Technical Program Committee member for many IEEE sponsored and cosponsored workshops, symposiums, and conferences on signal processing and wireless communications, including Co-organizer and General Co-chairman of IEEE SPAWC 2001, and Co-Chair of Signal Processing for Communications (SPC) Symposium, ChinaCOM 2008, and Lead Co-Chair of SPC Symposium, ChinaCOM 2009. He was an Associate Editor of the IEEE TRANSACTIONS ON SIGNAL PROCESSING (May 2001–April 2006), the IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS II (January 2006–December /2007), and a member of Editorial Board of the *EURASIP Signal Processing Journal* (June 2005–May 2008), and an editor (July 2003–December 2005), as well as a Guest Editor (2006) of the *EURASIP Journal on Applied Signal Processing*. LETTERS and the IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS I, and a member of IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS I, and a member of IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS I, and a member of IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS I, and a member of IEEE Signal Processing Committee on Signal Processing Theory and Methods.